


# SPECIFICATIONS:

MODEL		DPS - 2010		DPS - 4005		DPS - 6003	
		CH1	CH2	CH1	CH2	CH1	CH2
	OUTPUT RATINGS	V	0.00 ~ 20.00V	5V	0.00 ~ 40.00V	5V	0.00 ~ 60.00V
		A	0.000 ~ 9.990A	3A	0.000 ~ 5.000A	3A	0.000 ~ 3.500A
	OUTPUT RESOLUTION	V	10mV		10mV		20mV
		A	4mA		2mA		2mA
POWER	RIPPLE & NOISE	V	20mV rms				
		A	10mA rms				
	LINE REGULATION	V	≤ 0.05%				
		A	≤ 0.05%				
	LOAD REGULATION	V	≤ 10mV				
		A	≤ 5mA				
PROGRAMMABLE	PROGRAM ACCURACY		± 0.05% ± 3 CNT		± 0.05% ± 4 CNT		± 0.05% ± 5 CNT
			± 0.3% ± 10 CNT		± 0.15% ± 5 CNT		± 0.15% ± 5 CNT
METER	READBACK RESOLUTION		10mV		10mV		20mV
			4mA		2mA		2mA
	READBACK ACCURACY		± 0.05% ± 3 CNT		± 0.05% ± 4 CNT		± 0.05% ± 5 CNT
			± 0.3% ± 10 CNT		± 0.15% ± 5 CNT		± 0.15% ± 5 CNT
	AC INPUT	V	115V	230V			
		A	4.16A	2.17A			
SYSTEM	ENVIRONMENTAL	0°C ~ 40°C Operating Temperature					
		80% Max. Non-condensing					
	WEIGHT (Kgs)	N.W. 4.1Kgs					
		G.W. 4.4Kgs					
	DIMENSION	295(D) * 270(W) * 130(H) Unpack(mm)					
		380(D) * 340(W) * 190(H) Pack (mm)					

\* Specifications are subject to changes w/o notice



Manufacturer & Exporter

**TRUEFUL ELECTRONICS CO., LTD.**  
 Tahu Science Park 11F, No. 29-1, Lane 169, Kang Ning St.  
 Hsi Chih, Taipei Hsien 221 Taiwan R.O.C.  
 TEL: 886-2-26922188  
 FAX: 886-2-26922189  
 E-mail: trueful@ms6.hinet.net  
 http://www.trueful.com.tw

V04.9